

# FM601

- 4 wide grooves and asymmetric tread design improve wet performance and resist hydroplaning.
- High stiffness center ribs enhance handling performance, driving stability during high-speed driving.
- Optimum surface split siping is applied for 3D block design and enhanced wet/dry traction performance.
- Increased shoulder block stiffness and pressure distribution deliver maximum grip during high-speed cornering.
- Groove designed for optima hydro performance from the rib contact surface through to inter zone main groove.



INCH	SIZE	L.I. / S.R.	R.W inch	O.D. mm	S.W. mm	UTQG				NOISE GRADE
13"	155/65R13	73T	4.5	532	157	400 AA	D	B	69	B
	155/70R13	75T	4.5	548	157	360 AA	D	B	69	B
	155/80R13	79T	4.5	578	157	400 AA	D	B	69	B
	165/65R13	77H	5.0	544	170	360 AA	D	B	69	B
	165/70R13	79T	5.0	562	170	360 AA	D	B	69	B
	165/80R13	83T	4.5	594	165	360 AA	D	B	69	B
	175/60R13	77T	5.0	540	177	360 AA	D	B	69	B
	175/70R13	82T	5.0	576	177	360 AA	D	B	69	B
14"	185/70R13	86H	5.5	590	189	400 AA	C	B	69	B
	155/65R14	75T	4.5	558	157	360 AA	D	B	69	B
	155/70R14	77T	4.5	574	157	360 AA	D	B	69	B
	165/60R14	75H	5.0	554	170	400 AA	D	B	69	B
	165/65R14	79T	5.0	570	170	400 AA	D	B	69	B
	165/70R14	81T	5.0	588	170	360 AA	D	B	69	B
	175/65R14	82T	5.0	584	177	400 AA	D	B	69	B
	175/65R14	82H	5.0	584	177	400 AA	D	B	69	B
	175/70R14	84H	5.0	602	177	360 AA	C	B	69	B
	185/50R14	77V	6.0	542	194	400 AA	D	B	69	B
	185/55R14	80H	6.0	560	194	360 AA	D	B	69	B
	185/60R14	82H	5.5	578	189	400 AA	D	B	69	B
	185/65R14	86H	5.5	596	189	400 AA	C	B	69	B
	185/70R14	88H	5.5	616	189	400 AA	C	B	69	B
	195/60R14	86H	6.0	590	201	400 AA	C	B	69	B
	195/65R14	89H	6.0	610	201	400 AA	C	B	69	B
	195/70R14	91H	6.0	630	201	400 AA	C	B	69	B
	205/60R14	88H	6.0	602	209	400 AA	C	B	69	B
205/70R14	95H	6.0	644	209	400 AA	C	B	69	B	
215/70R14	96H	6.5	658	221	400 AA	C	B	69	B	
15"	155/60R15	74T	4.5	567	157	400 AA	D	B	69	B
	165/60R15	81H XL	5.0	579	170	400 AA	D	B	69	B
	165/65R15	81T	5.0	595	170	400 AA	D	B	69	B
	175/55R15	77T	5.5	573	182	360 AA	D	B	69	B
	175/60R15	81H	5.0	591	177	360 AA	D	B	69	B
	175/65R15	84H	5.0	609	177	360 AA	C	B	69	B

# FM601

- 4 wide grooves and asymmetric tread design improve wet performance and resist hydroplaning.
- High stiffness center ribs enhance handling performance, driving stability during high-speed driving.
- Optimum surface split siping is applied for 3D block design and enhanced wet/dry traction performance.
- Increased shoulder block stiffness and pressure distribution deliver maximum grip during high-speed cornering.
- Groove designed for optima hydro performance from the rib contact surface through to inter zone main groove.



INCH	SIZE	L.I. / S.R.	R.W inch	O.D. mm	S.W. mm	UTQG				NOISE GRADE
15"	185/55R15	82V	6.0	585	194	400 AA	D	B	69	B
	185/60R15	84H	5.5	603	189	400 AA	C	B	69	B
	185/60R15	88HXL	5.5	603	189	400 AA	C	B	69	B
	185/65R15	88T	5.5	621	189	400 AA	C	B	69	B
	185/65R15	88H	5.5	621	189	400 AA	C	B	69	B
	195/65R15	91H	6.0	635	201	400 AA	C	B	69	B
	195/65R15	91V	6.0	635	201	400 AA	C	B	69	B
	195/65R15	95T	6.0	635	201	400 AA	C	B	69	B
	195/50R15	82V	6.0	577	201	400 AA	D	B	69	B
	195/55R15	85V	6.0	595	201	400 AA	C	B	69	B
	195/60R15	88H	6.0	615	201	400 AA	C	B	69	B
	195/60R15	88V	6.0	615	201	400 AA	C	B	69	B
	205/60R15	91V	6.0	627	209	400 AA	C	B	69	B
	205/65R15	94V	6.0	647	209	400 AA	C	B	69	B
	205/70R15	96H	6.0	669	209	400 AA	C	B	69	B
	215/60R15	94H	6.5	639	221	400 AA	C	B	69	B
	215/65R15	96H	6.5	661	221	400 AA	C	B	69	B
215/70R15	98H	6.5	683	221	400 AA	C	B	69	B	
225/60R15	96V	6.5	651	228	400 AA	C	B	69	B	
16"	175/50R16	77V	5.5	582	182	320 AA	D	B	69	B
	175/60R16	82H	5.0	616	177	360 AA	D	B	69	B
	185/50R16	81V	6.0	592	194	320 AA	D	B	69	B
	185/55R16	87V XL	6.0	610	194	320 AA	C	B	69	B
	195/60R16	89H	6.0	640	201	400 AA	C	B	69	B
	205/45ZR16	87W XL	7.0	590	206	320 AA	C	B	69	B
	205/55R16	91V	6.5	632	214	320 AA	C	B	69	B
	205/55ZR16	91W	6.5	632	214	320 AA	C	B	69	B
	205/55ZR16	94W	6.5	632	214	320 AA	C	B	69	B
	205/60R16	92H	6.0	652	209	400 AA	C	B	69	B
	205/60R16	92V	6.0	652	209	400 AA	C	B	69	B
	205/65R16	95H	6.0	672	209	400 AA	C	B	69	B
	215/55ZR16	97W XL	7.0	642	226	320 AA	C	B	69	B
	215/60R16	95V	6.5	664	221	400 AA	C	B	69	B

# FM601

- 4 wide grooves and asymmetric tread design improve wet performance and resist hydroplaning.
- High stiffness center ribs enhance handling performance, driving stability during high-speed driving.
- Optimum surface split siping is applied for 3D block design and enhanced wet/dry traction performance.
- Increased shoulder block stiffness and pressure distribution deliver maximum grip during high-speed cornering.
- Groove designed for optima hydro performance from the rib contact surface through to inter zone main groove.



INCH	SIZE	L.I. / S.R.	R.W inch	O.D. mm	S.W. mm	UTQG				NOISE GRADE
16"	215/60R16	99V XL	6.5	664	221	400 AA	C	B	69	B
	215/65R16	98	6.5	686	221	400 AA	C	B	69	B
	225/50R16	92V	7.0	632	233	320 AA	C	B	69	B
	225/50ZR16	96W XL	7.0	632	233	320 AA	C	B	69	B
	225/55ZR16	99W XL	7.0	654	233	320 AA	C	B	69	B
	225/60R16	98H	6.5	676	228	400 AA	C	B	69	B
235/60R16	100H	7.0	688	240	400 AA	C	B	69	B	
17"	195/40R17	81W XL	7.0	588	200	320 AA	D	B	69	B
	195/45R17	85W XL	6.5	608	195	320 AA	C	B	69	B
	205/40ZR17	84W XL	7.5	596	212	320 AA	C	B	69	B
	205/45ZR17	88W XL	7.0	616	206	320 AA	C	B	69	B
	205/50ZR17	93W XL	6.5	638	214	320 AA	C	B	69	B
	205/55ZR17	95W XL	6.5	658	214	320 AA	C	B	69	B
	215/40ZR17	87W XL	7.5	604	218	320 AA	C	B	69	B
	215/45ZR17	91W XL	7.0	626	213	320 AA	C	B	69	B
	215/50ZR17	95W XL	7.0	648	226	320 AA	C	B	69	B
	215/55ZR17	98W XL	7.0	668	226	320 AA	C	B	69	B
	225/45ZR17	94W XL	7.5	634	225	320 AA	C	B	69	B
	225/50R17	94V	7.0	658	233	320 AA	C	B	69	B
	225/50ZR17	98W XL	7.0	658	233	320 AA	C	B	69	B
	225/55ZR17	101W XL	7.0	680	233	320 AA	C	B	69	B
	235/45ZR17	97W XL	8.0	644	236	320 AA	C	B	69	B
	235/50R17	100W XL	7.5	668	245	320 AA	C	B	69	B
	235/55R17	103V XL	7.5	690	245	320 AA	C	B	69	B
	245/40R17	95W XL	8.5	628	248	320 AA	C	B	69	B
245/45ZR17	99W XL	8.0	652	243	320 AA	C	B	69	B	
18"	215/35R18	84W XL	7.5	607	218	320 AA	C	B	69	B
	215/40ZR18	89W XL	7.5	629	218	320 AA	C	B	69	B
	215/45ZR18	93W XL	7.0	651	213	320 AA	C	B	69	B
	225/35ZR18	87Y XL	8.0	615	230	320 AA	C	B	69	B
	225/40ZR18	92W XL	8.0	637	230	320 AA	C	B	69	B
	225/45ZR18	95W XL	7.5	659	225	320 AA	C	B	69	B
	235/40ZR18	95W XL	8.5	645	241	320 AA	C	B	69	B

# FM601

- 4 wide grooves and asymmetric tread design improve wet performance and resist hydroplaning.
- High stiffness center ribs enhance handling performance, driving stability during high-speed driving.
- Optimum surface split siping is applied for 3D block design and enhanced wet/dry traction performance.
- Increased shoulder block stiffness and pressure distribution deliver maximum grip during high-speed cornering.
- Groove designed for optima hydro performance from the rib contact surface through to inter zone main groove.



INCH	SIZE	L.I. / S.R.	R.W inch	O.D. mm	S.W. mm	UTQG				NOISE GRADE
18"	235/45ZR18	98W XL	8.0	669	236	320 AA	C	B	69	B
	235/50ZR18	101W XL	7.5	693	245	320 AA	C	B	69	B
	235/55ZR18	104V XL	7.5	715	245	320 AA	C	B	69	B
	245/35ZR18	92Y XL	8.5	629	248	320 AA	C	B	69	B
	245/40ZR18	97W XL	8.5	653	248	320 AA	C	B	69	B
	245/45ZR18	100W XL	8.0	677	243	320 AA	C	B	69	B
	245/50ZR18	104W XL	7.5	703	253	320 AA	C	B	69	B
	255/35ZR18	94W XL	9.0	635	260	320 AA	C	B	73	B
	255/40ZR18	99Y XL	9.0	661	260	320 AA	C	B	73	B
	255/45ZR18	103W XL	8.5	687	255	320 AA	C	B	73	B
	255/55ZR18	109W XL	8.0	737	265	320 AA	C	B	73	B
	265/35ZR18	97Y XL	9.5	643	271	320 AA	C	B	73	B
275/35ZR18	99Y XL	9.5	649	278	320 AA	C	B	73	B	
19"	215/35ZR19	85Y XL	7.5	633	218	320 AA	C	B	69	B
	225/35ZR19	88W XL	8.0	641	230	320 AA	C	B	69	B
	235/35ZR19	91W XL	8.5	647	241	320 AA	C	B	69	B
	225/40ZR19	93Y XL	8.0	663	230	320 AA	C	B	69	B
	225/45ZR19	96Y XL	7.5	685	225	320 AA	C	B	69	B
	235/35ZR19	91W XL	8.5	647	241	320 AA	C	B	69	B
	235/40ZR19	96W XL	8.5	671	241	320 AA	C	B	69	B
	245/35ZR19	93W XL	8.5	655	248	320 AA	C	B	69	B
	245/40ZR19	98Y XL	8.5	679	248	320 AA	C	B	69	B
	245/45ZR19	102W XL	8.0	703	243	320 AA	C	B	69	B
	255/30ZR19	91W XL	9.0	637	260	320 AA	C	B	73	B
	255/35ZR19	96W XL	9.0	661	260	320 AA	C	B	73	B
	255/40ZR19	100W XL	9.0	687	260	320 AA	C	B	73	B
	255/45R19	104Y XL	8.5	713	255	320 AA	C	B	73	B
	265/30R19	93Y XL	9.5	643	271	320 AA	C	B	73	B
	275/30R19	96Y XL	9.5	649	278	320 AA	C	B	73	B
	275/35R19	100Y XL	9.5	675	278	320 AA	C	B	73	B
275/40R19	105Y XL	9.5	703	278	320 AA	C	B	73	B	
275/45R19	108Y XL	9.0	731	273	320 AA	C	B	73	B	

# FM601

- 4 wide grooves and asymmetric tread design improve wet performance and resist hydroplaning.
- High stiffness center ribs enhance handling performance, driving stability during high-speed driving.
- Optimum surface split siping is applied for 3D block design and enhanced wet/dry traction performance.
- Increased shoulder block stiffness and pressure distribution deliver maximum grip during high-speed cornering.
- Groove designed for optima hydro performance from the rib contact surface through to inter zone main groove.



INCH	SIZE	L.I. / S.R.	R.W inch	O.D. mm	S.W. mm	UTQG				NOISE GRADE
20"	225/35R20	90W XL	8.0	666	230	320 AA	C	B	69	B
	235/30R20	88Y XL	8.5	650	241	320 AA	C	B	69	B
	245/30R20	90Y XL	8.5	656	248	320 AA	C	B	69	B
	245/35ZR20	95W XL	8.5	680	248	320 AA	C	B	69	B
	245/40R20	99Y XL	8.5	704	248	320 AA	C	B	69	B
	255/30R20	92W XL	9.0	662	260	320 AA	C	B	69	B
	255/35R20	97Y XL	9.0	686	260	320 AA	C	B	73	B
	275/30R20	97Y XL	9.5	674	278	320 AA	C	B	73	B
275/35R20	102W XL	9.5	700	278	320 AA	C	B	69	B	
22"	295/40R22	112W XL	10.5	795	301	320 AA	C	B	69	B

